



- SPECIFICATIONS**
- FRAME W/ CAPFLASHING (CORNERS FULL WELDED)
F-40 - 14 GAUGE GALVANNEAL STEEL
F-50 - 11 GAUGE ALUMINUM
 - PINTLE HINGE
 - GASKET (ALL AROUND COVER)
 - COVER GAUGE
F-40 - 11 GAUGE ALUMINUM
F-50 - 11 GAUGE ALUMINUM
 - COVER LINER
F-40 - 18 GAUGE ALUMINUM
F-50 - 18 GAUGE ALUMINUM
 - SPRING LIFTING MECHANISM
 - 1" RIGID FIBERBOARD INSULATION
 - SLAM LATCH
 - INSIDE AND OUTSIDE HANDLES W/PADLOCK HASPS
 - ARM GUIDE BRACKET
 - 1" THICK FIBERGLASS COVER INSULATION
 - HEAVY DUTY HOLD OPEN ARM W/ RED VINYL GRIP
 - NEOPRENE GASKET
 - LOCK STRIKE & PADLOCK HASP
 - BILCLIP® FLASHING SYSTEM
 - GUIDE ARM

SHOP FINISH:
 STEEL: RED OXIDE PRIMER
 ALUMINUM: MILL FINISH
 HARDWARE: ZINC PLATED/CHROMATE SEALED
 (UNLESS OTHERWISE SPECIFIED)

THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.

CUSTOMER: _____

P.O. NO: _____

JOB: _____

TAG: _____

SALES REP: _____

APPROVED BY: _____

DATE: _____

Manufacturers of Doors for Special Services
Bilco® THE BILCO COMPANY
 New Haven, Connecticut 06505

SINGLE LEAF ROOF SCUTTLE
TYPE F SIZE 4'-0" x 4'-0"
 WIDTH x LENGTH

QTY	TYPE	METAL
<input type="checkbox"/>	F-40	ALUM. COVER/STEEL FRAME
<input type="checkbox"/>	F-50	ALUM. COVER/ALUM. FRAME

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.