



COMMERCIAL PRODUCTS

- ☐ Roof Access Hatches
- ☐ Automatic Smoke Vents
- ☐ Safety Products



**INNOVATIVE ACCESS
SOLUTIONS, LONG-LASTING
PERFORMANCE.**

A Part of Something BiggerSM

Quanex



THE BILCO COMPANY IS NOW PART OF SOMETHING BIGGER

The BILCO Company is now a part of Quanex. Quanex (NYSE: NX), a global, publicly traded manufacturing company serving OEMs in the fenestration, hardware, cabinetry, solar, refrigeration, security, construction, and outdoor products markets. **We are A Part of Something BiggerSM.**

We are dedicated to:

- Improving the performance, sustainability and aesthetics of end products through continuous innovation.
- Helping customers achieve greater production efficiencies.
- Giving back to communities where we operate.
- Enhancing shareholder value.
- Helping our employees learn, grow and thrive.

All over the world, from the Dubai skyline to neighborhood homes, Quanex plays a crucial part. We are a community of talented employees working together as one source for quality building components. We're helping to make your end products—and your business—better.

Our solutions include insulating glass spacers, vinyl profiles, window and door screens, hardware, cabinet components, fenestration components, vinyl extrusions, rubber extrusions, kitchen components, bathroom components, millwork, security products, and beyond. One solution at a time, we're striving to build a brighter future for our customers and communities. Globally trusted, driven by innovation, and fueled by technology, we're always thinking about what's next. And we're ready for it.

Quanex Mission

To positively impact our customers, employees and shareholders and put them at the center of everything we do, through innovation technology, best-in-class customer service and excellent returns.

The BILCO Company

P.O. Box 1203
New Haven, CT 06505

Phone: (800) 366-6530
Fax (203) 535-1582

Email: commercial@BILCO.com
Web: BILCO.com

The BILCO Company reserves the right to make design changes or to withdraw designs and products shown throughout this catalog without notice as we deem advisable.

©2025 The BILCO Company, New Haven, Connecticut 06505



Index

Roof Access Hatches

Ladder Access	5
Ship or Steep Stair Access	6
Service or Full Service Access	7
Equipment Access	8
Specialty Hatches	10

Automatic Smoke Vents

Double Leaf	13
Single Leaf	14
Natural Daylighting	15
Acoustically Sound Rated	16

Safety Products	17
---------------------------	----

Roofing Product Options	18
-----------------------------------	----

Product details and specifications are readily available by visiting our download center on BILCO.com

U.S. and International BILCO patents issued:

5,373,665	5,565,274	5,960,596	6,260,305	6,672,020	10,000,944
5,554,433	5,927,012	6,041,553	6,347,818	6,931,793	

Other U.S. and International patents issued and pending.



ROOF ACCESS HATCHES

BILCO roof hatches provide safe and convenient access to roof areas by means of an interior ladder, ship stair or service stair. A variety of special sizes are also available to provide an accessible way to install or remove large pieces of equipment from a building. All products feature engineered lift assistance for easy one-hand operation.



Benefits

- Easy, one-hand operation
- Weathertight performance
- Energy efficient
- Installs quickly and easily
- Convenient and secure access to roof areas
- Durable construction
- Custom sizes and options readily available

Features

- Engineered lift assistance
- Heavy-gauge construction
- Positive slam latch with interior and exterior padlock hasps
- Fully insulated and gasketed
- Corrosion resistant hardware
- Bilclip® Flashing System for ease of installation on single-ply roofing
- Available with Miami-Dade County and Florida Product Approval
- Pre-punched capflashing to receive the Bil-Guard® 2.0 Hatch Safety Railing System (see page 17 for more information)



TYPE S
TYPE E

Ladder Access

The easy one-hand-only operation to the fully opened or closed position provides the user the security of having the other hand firmly on the ladder at all times. Available in galvanized steel, aluminum or stainless steel construction. Aluminum products are also available in a thermally broken design that offers superior energy efficiency and resists condensation.

Material

- Steel: 14 gauge (1.9mm) galvalume steel
- Aluminum: 11 gauge (2.3mm)
- Stainless Steel: 14 gauge (1.9mm) Type 304 stainless

Insulation

- 1" (25mm) fiberglass insulation in cover and 1" fiberboard insulation in curb
- 3" (75mm) Polyisocyanurate (R = 20.3) in cover and curb (Thermally Broken Models)

Finish

- Steel: Alkyd base red oxide primer
- Aluminum: Mil finish
- Stainless Steel: Bead blast finish
- See page 18 for custom finish options

Hardware

- Zinc plated/chromate sealed
- Type 316 stainless steel



TYPE S-50TB
TYPE E-50TB
THERMALLY BROKEN
R-20+ INSULATION

Specialty Roof Hatches *(see pages 10-11 for more information)*

- Daylighting with polycarbonate skylight
- Retrofit mounting
- Security Series

See pages 18-19 for a complete list of curb, finish and other special options.



Florida Product Approval


Type S-20 and S-50 Only

TYPE	INCHES	MM	MATERIAL	INSULATION	THERMALLY BROKEN
S-20	36 x 30	914 x 762	Steel	1" (25mm)	No
S-50	36 x 30	914 x 762	Aluminum	1" (25mm)	No
S-50TB	36 x 30	914 x 762	Aluminum	3" (75mm)	Yes
S-90	36 x 30	914 x 762	Stainless Steel	1" (25mm)	No
E-20	36 x 36	914 x 914	Steel	1" (25mm)	No
E-50	36 x 36	914 x 914	Aluminum	1" (25mm)	No
E-50TB	36 x 36	914 x 914	Aluminum	3" (75mm)	Yes
E-90	36 x 36	914 x 914	Stainless Steel	1" (25mm)	No


Type S-40 and E-40 models are available in steel curb and aluminum cover.



ROOF ACCESS HATCHES



Type NB
Type NB-HZ



Type NB-50TB
Thermally Broken
R-20+ Insulation

Ship or Steep Stair Access

BILCO Ship Stair access hatches are ideal for installations where frequent use may be expected. Permits easier movement of maintenance personnel, tools, and equipment. Available in galvanized steel, aluminum or stainless steel construction. Aluminum products are also available in a thermally broken design that offers superior energy efficiency and resists condensation.

Material

- Steel: 14 gauge (1.9mm) galvalume steel
- Aluminum: 11 gauge (2.3mm)
- Stainless Steel: 14 gauge (1.9mm) Type 304 stainless

Insulation

- 1" (25mm) fiberglass insulation in cover and 1" fiberboard insulation in curb
- 3" (75mm) Polyisocyanurate (R = 20.3) in cover and curb (Thermally Broken Models)

Finish

- Steel: Alkyd base red oxide primer
- Aluminum: Mil finish
- Stainless Steel: Bead blast finish
- See page 18 for custom finish options

Hardware

- Zinc plated/chromate sealed
- Type 316 stainless steel

Specialty Roof Hatches

(see pages 10-11 for more information)

- Daylighting with polycarbonate skylight
- Retrofit mounting
- Security Series

See pages 18-19 for a complete list of curb, finish and other special options.



Type NB-20HZ and NB-50HZ only

TYPE	INCHES	MM	CURB MATERIAL	COVER MATERIAL	INSULATION	THERMALLY BROKEN
NB-20	30 x 54	762 x 1372	Steel	Steel	1" (25mm)	No
NB-20HZ	30 x 54	762 x 1372	Steel	Steel	1" (25mm)	No
NB-50	30 x 54	762 x 1372	Aluminum	Aluminum	1" (25mm)	No
NB-50TB	30 x 54	762 x 1372	Aluminum	Aluminum	3" (75mm)	Yes
NB-50HZ	30 x 54	762 x 1372	Aluminum	Aluminum	1" (25mm)	No
NB-90	30 x 54	762 x 1372	Stainless Steel	Stainless Steel	1" (25mm)	No

Type NB-40 models are available in steel curb and aluminum cover.



Type L



Type L-50TB
Thermally Broken
R-20+ Insulation

Service or Full Service Access

BILCO Service Stair access roof hatches are available in galvanized steel, aluminum or stainless steel construction to meet any job requirements. Aluminum products are also available in a thermally broken design that offers superior energy efficiency and resists condensation.

Material

- Steel: 14 gauge (1.9mm) galvalume steel
- Aluminum: 11 gauge (2.3mm)
- Stainless Steel: 14 gauge (1.9mm) Type 304 stainless

Insulation

- 1" (25mm) fiberglass insulation in cover and 1" fiberboard insulation in curb
- 3" (75mm) Polyisocyanurate (R = 20.3) in cover and curb (Thermally Broken Models)

Finish

- Steel: Alkyd base red oxide primer
- Aluminum: Mil finish
- Stainless Steel: Bead blast finish
- See page 18 for custom finish options

Hardware

- Zinc plated/chromate sealed
- Type 316 stainless steel

Specialty Roof Hatches

(see pages 10-11 for more information)

- Daylighting with polycarbonate skylight
- Retrofit mounting
- Security Series

See pages 18-19 for a complete list of curb, finish and other special options.



Type L-20HZ and L-50HZ only

TYPE	INCHES	MM	MATERIAL	INSULATION	THERMALLY BROKEN
L-20	30 x 96	762 x 2438	Steel	1" (25mm)	No
L-50	30 x 96	762 x 2438	Aluminum	1" (25mm)	No
L-50TB	30 x 96	762 x 2438	Aluminum	3" (75mm)	Yes
L-90	30 x 96	762 x 2438	Stainless Steel	1" (25mm)	No

Type L-40 models are available in steel curb and aluminum cover.



ROOF ACCESS HATCHES

Equipment Access

Larger openings provide an easily accessible means for equipment to be installed or removed from a building. Equipment access roof hatches are available in steel, aluminum and stainless steel construction and in one standard single leaf size [Type F, 48" x 48" (1219mm x 1219mm)]. Special single leaf sizes (Type SS) are available and are recommended for widths up to 5'0" (1524mm). For larger openings, specify double leaf construction (Type D). For best operation, specify aluminum construction for single leaf hatches over 3'0" (914mm) wide and double leaf hatches over 7'0" (2134mm) in width.



Benefits

- Easy, one-hand operation
- Weathertight performance
- Energy efficient
- Installs quickly and easily
- Convenient and secure access to roof areas
- Durable construction
- Custom sizes and options readily available

Features

- Engineered lift assistance
- Heavy-gauge construction
- Positive slam latch with interior and exterior padlock hasps
- Fully insulated and gasketed
- Corrosion resistant hardware
- Bilclip® Flashing System for ease of installation on single-ply roofing
- Pre-punched capflashing to receive the Bil-Guard® 2.0 Hatch Safety Railing System (see page 17 for more information)



Type F
48" x 48" (1219mm x 1219mm)
Custom sizes available

Product Options

BILCO Equipment access roof hatches are available in galvanized steel, aluminum, stainless steel and copper construction to meet any job requirements.

Material

- Steel: 14 gauge (1.9mm) galvalume steel
- Aluminum: 11 gauge (2.3mm)
- Stainless Steel: 14 gauge (1.9mm) Type 304

Insulation

- 1" (25mm) fiberglass insulation in cover and 1" fiberboard insulation in curb
- 3" (75mm) Polyisocyanurate (R = 20.3) in cover and curb (Thermally Broken Models*)

Finish


- Steel: Alkyd base red oxide primer
- Aluminum: Mil finish
- Stainless Steel: Bead blast finish
- See page 18 for custom finish options

Hardware

- Zinc plated/chromate sealed
- Type 316 stainless steel

See pages 18-19 for a complete list of curb, finish and other special options.

**Thermally broken models are not available in double leaf design*



Type F-50TB
48" x 48" (1219mm x 1219mm)
Thermally Broken
R-20+ Insulation
Custom sizes available



Type D
Special Size



ROOF ACCESS HATCHES

Specialty Roof Hatches

BILCO also has a long history of providing specialty access solutions for virtually any application. Whether for extreme environments, secure facilities, retrofit applications or day-lighting, there is a BILCO roof hatch ready to do the job. Along with an extensive array of available roof hatch options (see pages 18-19), BILCO also offers custom-engineering capabilities to ensure safe and reliable roof access no matter what the application.




Benefits

- Easy, one-hand operation
- Weathertight performance
- Energy efficient
- Installs quickly and easily
- Convenient and secure access to roof areas
- Durable construction
- Custom sizes and options readily available

Features

- Engineered lift assistance
- Heavy-gauge construction
- Positive slam latch with interior and exterior padlock hasps
- Fully insulated and gasketed
- Corrosion resistant hardware
- Bilclip® Flashing System for ease of installation on single-ply roofing
- Pre-punched capflashing to receive the Bil-Guard® 2.0 Hatch Safety Railing System (see page 17 for more information)



Type GS Daylighting Roof Hatch

All the security and convenience of the Type S roof hatch with the added benefits of a skylight. GS Roof Hatches feature aluminum construction and virtually indestructible polycarbonate domes. Domes are available in clear and translucent and double domes can be specified. Specify Type GSS for custom single leaf sizes.




Security Series Roof Hatch

Constructed of heavier gauge materials for high security applications such as prisons, banks, embassies, and pharmaceutical buildings. Roof hatches can be fabricated for field installation of many leading brands of security locks. Other options include security glazing and gunports (see page 19).

VersaMount® Retrofit Roof Hatch


The VersaMount® replacement hatch allows you to replace a damaged roof hatch without re-roofing. Simply remove the cover from the damaged hatch and place the VersaMount® hatch on top of the existing curb. The low-profile curb features a built-in flange and apron and innovative anchor clip system to ensure a fast, secure and weathertight installation. Available in a number of standard sizes.



Job-Built
Concrete Curbs



Existing Roof Hatch
or Job-Built/Prefab
Metal Curbs



Job-Built
Wood Curbs





AUTOMATIC SMOKE VENTS

Automatic Smoke Vents

Automatic Smoke Vents protect property and aid firefighters in bringing a fire under control by removing smoke, heat, and gases from a burning building. Ideally suited for large expanses of unobstructed space such as factories, warehouses, auditoriums, and retail facilities smoke vents are available in a number of standard UL-listed sizes.




Benefits

- Increased evacuation time and decreased risk of smoke inhalation and damage
- Enhanced visibility to allow firefighters to quickly locate the fire
- Protection against secondary ignitions and lateral fire spread
- Exhausting of noxious and potentially explosive fumes
- Structure protection from damaging heat
- Reduced damage to building contents

Features

- Fully insulated and gasketed for weathertight performance.
- Thermolatch® II latching mechanism with curb mounted fusible link housing for quick and easy resetting at the roof level
- Exterior and interior pull release handles for manual operation
- Covers open against a 10 psf (49 kg/m²) snow/wind load and automatically lock in the open position upon vent activation
- Bilclip® Flashing System for ease of installation on single-ply roofing
- Pre-punched capflashing to receive the Bil-Guard® 2.0 Hatch Safety Railing System (see page 17 for more information)
- Complies with UL790 Class A and UL793
- Available in a number of UL-approved sizes



Type DSH
Double Leaf

Double Leaf

BILCO smoke vents feature a positive hold/release mechanism controlled by a single UL-listed 165°F (74°C) fusible link designed to hold the covers closed against a 90 psf (438 kg/m²) wind uplift force. Smoke vents are provided with interior and exterior pull release cables to manually open vent covers. Aluminum products are also available in a thermally broken design that offers superior energy efficiency and resists condensation.

Material

- Steel: 14 gauge (1.9mm) galvalume steel
- Aluminum: 11 gauge (2.3mm) aluminum

Insulation

- 1" (25mm) fiberglass insulation in cover and 1" fiberboard insulation in curb
- 3" (75mm) Polyisocyanurate (R = 20.3) in cover and curb (Thermally Broken Models)

Finish


- Alkyd base red oxide primer (standard on all steel products)
- Mil finish (standard on all aluminum products)
- See page 18 for custom finish options

Hardware

- Zinc plated/chromate sealed hardware

Control Options

- Motor operation with push button control station
- Winch operation for remote opening and closing
- Electric release for smoke detector or fire alarm activation
- See page 19 for more information



Type DSH-TB
60" x 96" (1524mm x 2438mm)
Thermally Broken
R-20+ Insulation
Custom sizes available



Type DSH Standard Sizes

INCHES	MM	STEEL	STEEL CURB, ALUMINUM COVER	ALUMINUM
48 x 48	1219 x 1219	DSH4848	DSH4848A	DSH4848B
48 x 72	1219 x 1829	DSH4872	DSH4872A	DSH4872B
48 x 90	1219 x 2286	DSH4890	DSH4890A	DSH4890B
48 x 96	1219 x 2438	DSH4896	DSH4896A	DSH4896B
60 x 60	1524 x 1524	DSH6060	DSH6060A	DSH6060B
60 x 72	1524 x 1829	DSH6072	DSH6072A	DSH6072B
60 x 84	1524 x 2134	DSH6084	DSH6084A	DSH6084B
60 x 96	1524 x 2438	DSH6096	DSH6096A	DSH6096B
60 x 120	1524 x 3048	DSH60120	DSH60120A	DSH60120B
66 x 66	1676 x 1676	DSH6666	DSH6666A	DSH6666B
66 x 144	1676 x 3658	DSH66144*	DSH66144A*	DSH66144B*
72 x 72	1829 x 1829	DSH7272	DSH7272A	DSH7272B

*This size has four leaves.



AUTOMATIC SMOKE VENTS

Single Leaf

BILCO smoke vents feature a positive hold/release mechanism controlled by a single UL-listed 165°F (74°C) fusible link designed to hold the covers closed against a 90 psf (438 kg/m²) wind uplift force. Smoke vents are provided with interior and exterior pull release cables to manually open vent covers. Aluminum products are also available in a thermally broken design that offers superior energy efficiency and resists condensation.

Material

- Steel: 14 gauge (1.9mm) galvanized steel
- Aluminum: 11 gauge (2.3mm) aluminum

Insulation

- 1" (25mm) fiberglass insulation in cover and 1" fiberboard insulation in curb

Finish

- Alkyd base red oxide primer (standard on all steel products)
- Mil finish (standard on all aluminum products)
- See page 18 for custom finish options

Hardware

- Zinc plated/chromate sealed hardware

Control Options

- Motor operation with push button control station
- Winch operation for remote opening and closing
- Electric release for smoke detector or fire alarm activation
- See page 19 for more information



Type S-SV

Single Leaf
36" x 30"
(914mm X 762mm)
Custom sizes available



Type S-50SVTB

36" x 30"
(914mm x 762mm)

Type H-50SVTB

48" x 60"
(1219mm x 1524mm)

Thermally Broken

R-20+ Insulation
Custom sizes available



Natural Daylighting

Offers the same benefits as BILCO Automatic Smoke Vents with a built-in skylight for natural daylighting and to reduce energy costs. Featuring a polycarbonate cover design that resists UV degradation and offers superior insulation performance compared to traditional domes. The sloped or domed cover designs meet International Building Code Requirements.

Material

- Aluminum: 11 gauge (2.3mm) aluminum

Cover

- Single Leaf: clear polycarbonate dome or double domes
- Double leaf: Translucent multi-wall polycarbonate

Finish

- Mil finish (standard on all aluminum products)
- See page 18 for custom finish options

Hardware

- Stainless steel hinges and zinc plated/chromate sealed hardware




Type GS-SV

Single Leaf
36" X 30" (914mm x 762mm)
Custom sizes available



Lumivent®
Double Leaf



Features a multi-wall polycarbonate cover design that resists UV degradation and offers superior insulation performance compared to traditional domes

Lumivent Standard Sizes

TYPE	INCHES	MM	MATERIAL
LV4848B	48 x 48	1219 x 1219	Aluminum
LV4872B	48 x 72	1219 x 1829	Aluminum
LV4896B	48 x 96	1219 x 2438	Aluminum
LV6060B	60 x 60	1524 x 1524	Aluminum
LV6096B	60 x 96	1524 x 2438	Aluminum
LV66144B	66 x 144	1676 x 3658	Aluminum



AUTOMATIC SMOKE VENTS

Acoustically Sound Rated

BILCO's ACDSV acoustical smoke vent is designed to guard against noise intrusion while providing the security of automatic smoke venting. Acoustical vents feature industry-high OITC-46 and STC-50 sound ratings. They are ideal for concert halls, theaters and other interior applications that require limited noise from the outside. Vents are available in steel construction and in a number of UL-Listed standard sizes.

Material

- Steel: 14 gauge (1.9mm) galvalume steel

Insulation

- 4" (100 mm) mineral wool insulation

Finish

- Alkyd base red oxide primer
- See page 18 for custom finish options

Hardware

- Zinc plated/chromate sealed hardware


Control Options

- Motor operation with push button control station
- Winch operation for remote opening and closing
- Electric release for smoke detector or fire alarm activation
- See page 19 for more information

Sound Ratings


OITC-46
STC-50
ISO 140-18 (rain fall)

Type ACDSV Double Leaf



TYPE	INCHES	MM
ACDSV4848	48 x 48	1219 x 1219
ACDSV4896	48 x 96	1219 x 2438
ACDSV6096	60 x 96	1524x 2438
ACDSV66144	66 x 144*	1676 x 3658
ACDSV 7272	72 x 72	1829 x 1829

Thermolatch® II latching mechanism with curb mounted fusible link housing for quick and easy resetting at the roof level.



SAFETY PRODUCTS



Bil-Guard® 2.0 Safety Railing System

Bil-Guard® 2.0 is a fixed railing system that provides a permanent means of fall protection for hatch openings. Tested and proven to meet and exceed OSHA fall protection standards (29 CFR 1910.29), Bil-Guard® 2.0 features an innovative attachment system that does not penetrate the roofing membrane, installs quickly and easily using basic tools, and does not require special training or certification for proper installation. Corrosion-resistant aluminum rails and mounting brackets, along with stainless steel hardware, are ideal for any climate.

ROOF HATCH SIZE (width x length)		ROOF HATCH MODEL	BIL-GUARD 2.0 MODEL
INCHES	MM		
36 x 30	914 x 762	S	RL2-S
36 x 36	914 x 914	E	RL2-E
48 x 48	1219 x 1219	F	RL2-F
30 x 54	762 x 1372	NB	RL2-NB
30 x 96	762 x 2438	L	RL2-L

Railing system models available for thermally broken and custom size roof hatches and automatic smoke vents.



LadderUP® Safety Post

LadderUP® Safety Posts provide easier, safer ladder access through roof hatches, floor access doors and manholes. This telescoping post permanently mounts to the top two rungs of any fixed ladder, providing a positive hand-hold and enabling the user to enter or exit an opening in an upright and balanced position. The adjustable mounting hardware accommodates virtually any ladder rung size or spacing.

MODEL#	MATERIAL/FINISH	WEIGHT	
		LBS.	KG.
LU-1	Steel, yellow powder coat	24	11
LU-2	Steel, hot dip galvanized	24	11
LU-3	Type 304 Stainless Steel, sand blast finish	24	11
LU-4	Aluminum, mill finish	14	7

* This size has four leafs



ROOFING PRODUCT OPTIONS



Stainless Steel Hardware

Common Options

Stainless Steel Hardware

For installation in highly corrosive environments, Bilco smoke vents and roof hatches may be equipped with Type 316 stainless steel hardware, including: slam latch and lifting mechanism assemblies; hold-open and guide arms; and all brackets, hinges, pins, and fasteners.

Curb Options

All BILCO roofing products may be specified with either a curb liner (metal insulation liner of the same materials as the curb and capflashing) or a fully enclosed curb (full metal insulation liner of the same materials as the curb, which replaces the capflashing). Built-in louvers are available for roof hatches and for automatic smoke vents to meet elevator-shaft code requirements. Base flanges can be supplied with configurations for most brands of metal building roof panels. This option offers simplified installation, and includes a built-in self-drainage feature that eliminates water accumulation on the up-slope side.



Curb Modification for Metal Buildings



Built-in Louvers


Insulation

BILCO offers insulation options to enhance the energy efficiency of its roofing products. Standard roof products are supplied with standard 1" (25mm) fiberglass insulation in the covers and 1" (25mm) fiberboard insulation in the curb. When specified, products can be supplied with up to 2" (50mm) of Styrofoam or polyisocyanurate insulation in the cover and curb. Roof hatches and smoke vents can also be supplied in a thermally broken design that features 3" (75mm) of polyisocyanurate insulation in the cover and curb.

Special Finishes

- Factory applied powder coat paint finish is available on all steel and aluminum products. Finish is available in four standard colors and custom colors can be specified.
- Kynar® finish in custom colors (aluminum products only)
- Tnemec® finish in custom colors (steel and aluminum products)
- Clear anodized finish (aluminum products only)
- Custom finishes can also be specified

Powder Coat Standard Colors (Custom colors can also be specified)



White



Yellow



Bronze




Black



Winch Operation

Motorized or Winch Operation

To provide a convenient means of ventilating work areas, automatic smoke vents can be equipped with motor operators for actuation by remote push-button control or other electrical signal. They can also be furnished with rigging for manual winch operation at the floor level. Roof hatches can also be designed for motor or winch operation.



Motorized Operation

Other Options


In addition to standard options, BILCO's custom engineering capabilities can provide you with the exact roof product to meet your unique requirements.



Keyed Cylinder Locks



Detention Locks



Security Glazing



Electric Activation



Explosion Vents

Roof Hatch Options

Security

All BILCO roof hatches are supplied with a standard slam lock that includes an interior and exterior padlock hasp to prevent unauthorized access. BILCO also offers the options listed below for enhanced building security.

Keyed Cylinder Locks

Deadbolt cylinder locks provide keyed exterior access and are available with either keyed or turn knob interior access. Cylinder locks are an ideal security enhancement for many applications. For added security and weathertightness, the lock cylinder is accessed from the exterior through a gasketed, threaded deck plate.

Detention Locks

Detention locks provide keyed interior and exterior access and are ideal for correctional facilities and other buildings requiring a maximum level of security. For added security and weathertightness, the lock is accessed from the exterior through a gasketed, threaded deck plate. BILCO roof hatches can be prepared for field installation of many leading lock brands.

Emergency Egress Locks

BILCO roof hatches can be supplied with a panic lock for rapid egress in an emergency situation. Panic locks are available with keyed exterior access when specified.

Indicator Switches

Allow roof hatches to be wired into a building's alarm system. Indicator switches are curb mounted and send a signal to the alarm control panel when the hatch cover is opened.

Security Glazing

Security glazing allows personnel to visibly scan a secure area before entering or exiting a roof area. Glazing is available in a number of ballistic ratings with varying levels of security.

Smoke Vent Options

Electric Activation

Automatic smoke vents can be supplied with an electric Thermolatch® to allow the vents to be operated by a smoke detector or fire alarm control panel. In addition to electric activation, these vents feature fusible link activation and provisions for manual operation. Electric latches can be supplied for 115 VAC, 24 VAC, 220 VAC, and 24V DC power requirements.

Security Grilles

Heavy bars permanently welded in place across the curb opening. Bars are spaced to prevent building access and maximize ventilation area.

Explosion Vents

BILCO Type SV and Type DSH automatic smoke vents may also be equipped to operate as explosion vents or as combination fire/explosion vents. The explosion release mechanism is preset and factory-tested to release at between 25 lb/ft² and 30 lb/ft² – 122 kg/m² and 146 kg/m² of pressure on the underside of the covers. Not available on Type ACDSH or Lumivent models.

Lockable Enclosures

The exterior manual pull release may be supplied with an enclosure that can be padlocked to prevent unauthorized opening of the covers from the roof level.

Indicator Switches

Allow vents to be wired into a building's alarm system. Indicator switches are curb mounted and send a signal to the alarm control panel when the vent covers are opened.

The BILCO Company
P.O. Box 1203
New Haven, CT 06505
Phone: 800.366.6530
Fax: 203.535.1582

Sales

United States: commercial@BILCO.com
International: export@BILCO.com

Visit BILCO.com to find your local sales representative

BILCO.com

