



- SPECIFICATIONS**
- FRAME W/ CAPFLASHING (CORNERS FULL WELDED)
 - SS-20 - 14 GAUGE P.B. GALV. STEEL
 - SS-40 - 14 GAUGE P.B. GALV. STEEL
 - SS-50 - 11 GAUGE ALUMINUM
 - PINTLE HINGE
 - GASKET (ALL AROUND COVER)
 - COVER GAUGE
 - SS-20 - 14 GAUGE P.B. GALV. STEEL
 - SS-40 - 11 GAUGE ALUMINUM
 - SS-50 - 11 GAUGE ALUMINUM
 - COVER LINER
 - SS-20 - 22 GAUGE P.B. GALV. STEEL
 - SS-40 - 18 GAUGE ALUMINUM
 - SS-50 - 18 GAUGE ALUMINUM
 - LIFTING MECHANISM WITH REINFORCED COMPOSITE TUBES AND COMPRESSION SPRINGS
 - 1" RIGID FIBERBOARD INSULATION
 - SLAM LATCH
 - INSIDE AND OUTSIDE HANDLES W/ PADLOCK HASPS
 - ARM GUIDE BRACKET
 - 1" THICK FIBERGLASS COVER INSULATION
 - HOLD OPEN ARM W/ RED VINYL GRIP
 - NEOPRENE GASKET
 - LOCK STRIKE & PADLOCK HASP
 - BILCLIP® FLASHING SYSTEM
 - GUIDE ARM
 - HANDRAIL (1 1/4" SCH 40 PIPE, SAME MATERIAL AS COVER)
- SHOP FINISH:
 STEEL: RED OXIDE PRIMER
 ALUMINUM: MILL FINISH
 HARDWARE: ZINC PLATED & CHROMATE SEALED (UNLESS OTHERWISE SPECIFIED)

THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.

CUSTOMER:

P.O. N°

JOB:

SALES REP:

Manufacturers of Doors for Special Services
Bilco® THE BILCO COMPANY
 New Haven, Connecticut 06505

**SINGLE LEAF ROOF SCUTTLE
 MODIFIED FOR 56° LAPEYRE STAIR
 TYPE SS SIZE 2'-6" x 5'-10"**
 WIDTH x LENGTH

QTY	TYPE	METAL
<input type="checkbox"/>	SS-20	STEEL COVER/STEEL FRAME
<input type="checkbox"/>	SS-40	ALUM. COVER/STEEL FRAME
<input type="checkbox"/>	SS-50	ALUM. COVER/ALUM. FRAME

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.